

EFi75



Ventilatore/ Soffiante ATEX



12"/30cm | EFi75xx/EFi85xx Intrinsically Safe Blower/Exhauster

- Intrinsically safe – ATEX certified for use in adverse atmosphere
- Cast aluminum turbo blade is precision balanced
- Tough, chemical resistant ABS housing, carbon-filled to conduct static charges to ground
- IP65 rain tested switch enclosure "watertight"
- Integral 12"/30cm duct adapters
- Blow or exhaust hazardous/explosive gases safely
- Uses 12"/30cm or 8"/20cm duct, (8"/20cm requires optional adapter) conductive or non, suction or discharge
- IMPA Codes:
EB7201xx (110V) - 591506
EB7201xx-230 (230V) - 591506

Optional Accessories: Anti-Static Duct, Duct Carrying Bags, Cooling Collar

MODEL	EFi75xx	EFi85xx (60Hz)
Order #	EB7201XX	EB8201XX, EB8201XX-110
STOCK LOCATIONS		
FREE AIRFLOW	2,500cfm/4,250m³/hr	2,100cfm/3,570m³/hr
15ft/1-90° turn	1,664cfm/2,828.8m³/hr	1,397cfm/2,374.9m³/hr
15ft/2-90° turns	1,529cfm/2,599.3m³/hr	1,282cfm/2,179.4m³/hr
WEIGHT	44lbs/20kg	44lbs/20kg
DIMENSIONS (h/w/d)	16/15/16 in 406/381/406 mm	16/15/16 in 406/381/406 mm
NOISE	89dB	79.3dB
MOTOR	0.75Hp/0.56kW	0.85Hp/0.56kW
ELECTRIC	115/230VAC, 1ø, 50/60Hz	110/240VAC, 1ø, 50Hz
AMPS – START – RUN	115V: 37A 230V: 27A 115V: 7.2A 230V: 5A	110V: 37A 240V: 27A 110V: 7.2A 240V: 5A
UNIT CERTIFICATION	II 2 G Ex de IIB T6 BR-Ex de IIB T6	II 2 G Ex de IIB T6
MOTOR CERTIFICATION	II 2 G Ex d IIB	II 2 G Ex d IIB

Anti-Static Duct 15'/ 4.6m



Anti-Static Duct 25'/ 7.6m



UB20xx
EFi75xx/85xx
EFi50xx/120xx
EFi150xx
AFi75xx
AFi50xx

UB20xx
EFi75xx/85xx
EFi50xx/120xx
EFi150xx
AFi75xx
AFi50xx