

			PALLONI OTTURATORI			
					MASSIMA PRESSIONE DI GONFIAMENTO	
ART.	POLLICI	DIAMETRO NOMINALE	DIAMETRO INTERNO MAX	PSI	MILLIBAR	BAR
SRGB2	2"	50MM	55MM	15	1030	1,03
SRGB3	3"	75MM	84MM	15	1030	1,03
SRGB4	4"	100MM	112MM	15	1030	1,03
SRGB5	5"	125MM	138MM	15	1030	1,03
SRGB6	6"	150MM	168MM	15	1030	1,03
SRGB7	7"	175MM	192MM	15	1030	1,03
SRGB8	8"	200MM	224MM	14	960	0,96
SRGB9	9"	225MM	245MM	12	820	0,82
SRGB10	10"	250MM	276MM	10	690	0,68
SRGB12	12"	300MM	324MM	8	550	0,55
SRGB14	14"	350MM	368MM	7	480	0,48
SRGB15	15"	375MM	403MM	6,5	450	0,45
SRGB16	16"	400MM	417MM	6,5	440	0,45
SRGB18	18"	450MM	481MM	6	410	0,41
SRGB20	20"	500MM	520MM	5	340	0,34
SRGB21	21"	525MM	546MM	4,75	320	0,32
SRGB22	22"	550MM	559MM	4,25	310	0,31
SRGB24	24"	600MM	637MM	4	270	0,27
SRGB26	26"	650MM	669MM	3,75	250	0,25
SRGB27	27"	675MM	698MM	3,5	240	0,24
SRGB28	28"	700MM	737MM	3,5	240	0,24
SRGB30	30"	750MM	788MM	3,25	220	0,22
SRGB32	32"	800MM	813MM	3,25	220	0,22
SRGB36	36"	900MM	943MM	3	200	0,2
SRGB40	40"	1000MM	1021MM	2,5	170	0,17
SRGB42	42"	1050MM	1067MM	2,25	155	0,15
SRGB48	48"	1200MM	1252MM	2	130	0,14

PIPE

Tel. 02 - 44 50 542 Fax 02 - 44 54 226
 info@pipech.it - www.pipech.it
 Via Edison 13
 20090 Trezzano sul Naviglio MI