



PISTONI OTTURATORI 2 ANELLI



Specifiche tecniche

Double Seal Plugs insert further into the pipe giving greater stability in the pipeline. The two seals help to centralise the plug inside the pipe.

Thrustwashers fitted as standard on all plugs 9" (225mm) & above.

Zinc plated – corrosion resistant to 90 hours salt spray test.

Nominal pipe sizes, minimum & maximum pipe diameters each Plug will fit, maximum test pressure & weight of Plug are available below.

Pipe Size Internal Nominal Diameter		Will Fit Pipes With Internal Diameter		Minimum Insertion into Pipe	Overall length	Contact length	Diameter of waterway	Maximum allowable back pressure	Approx. Weight
Metric	Imperial	Minimum	Maximum						
40mm	1 1/2"	37mm	50mm	62mm	140mm		1/2"	30p.s.i	0.25kg
50mm	2"	50mm	61mm	66mm	140mm		1/2"	30p.s.i	0.28kg
65mm	2 1/2"	61mm	75mm	67mm	140mm		1/2"	30p.s.i	0.46kg
75mm	3"	73mm	85mm	68mm	140mm		1/2"	20p.s.i	0.49kg
89mm	3 1/2"	84mm	100mm	82mm	140mm		1/2"	15p.s.i	0.68kg
100mm	4"	94mm	108mm	76mm	140mm		1/2"	10p.s.i	0.70kg
114mm	4 1/2"	108mm	125mm	80mm	140mm		1/2"	10p.s.i	1.10kg
125mm	5"	124mm	139mm	74mm	140mm		1/2"	10p.s.i	1.25kg
150mm	6"	145mm	160mm	80mm	140mm		1/2"	10p.s.i	1.50kg
175mm	7"	175mm	200mm	92mm	210mm		1"	7p.s.i	2.65kg
200mm	8"	195mm	215mm	92mm	210mm		1"	7p.s.i	2.70kg
225mm	9"	210mm	230mm	92mm	210mm		1"	7p.s.i	3.45kg
250mm	10"	245mm	260mm	110mm	210mm		1"	7p.s.i	4.90kg
300mm	12"	296mm	320mm	170mm	210mm		1"	7p.s.i	6.75kg
350mm	14"	340mm	385mm	170mm	310mm		1"	5p.s.i	11.40kg
375mm	15"	370mm	415mm	200mm	310mm		1"	5p.s.i	12.20kg
400mm	16"	390mm	430	195mm	310mm		1"	5p.s.i	13.90kg
450mm	18"	448mm	495mm	250mm	410mm		1"	5p.s.i	18.50kg